

Technical sheet

MA10402

Air quality monitor

- TIME - 12/24H TIME FORMAT - INDOOR AND OUTDOOR TEMPERATURES -- INDOOR HUMIDITY – AIR QUALITY SENSOR – CO2 RATE – AIR QUALITY ALERT - WIRELESS TRANSMISSION 868MHZ - INDOOR AND OUTDOOR TEMPERATURES AND INDOOR HUMIDITIES + AIR QUALITY CAN BE TRANSMITTED TO YOUR PHONE



ref. MA10402



ref. WSTX47IT+

Specifications

MA10402

Hour Date ➔

- Manual time setting
- 12/24 hour time format

Indoor temperature ➔

- °C/°F
- From - 9.5 °C to + 59.5 °C
- Precision : 0.5 °C
- Min/Max
- 16 seconds measuring period

Indoor humidity ➔

- RH %
- From 20 % to 95 %
- Precision: 1%
- Accuracy : +/- 5 %
- 16 seconds measuring period

Outdoor temperature ➔

- °C/°F
- From – 39.9 °C to + 59.9 °C
- Precision: 0.1 °C
- Min/Max
- Measuring period : every 3 minutes

Transmission ➔

- 868 MHz frequency
- 100 meters in open range

Features ➔

- Air quality:
- From 450ppm to 3950ppm
- Resolution : 50ppm
- Colored variation on the base station
- 9 levels bargraph
-
- Low batteries indicators
- Table standing
-
- The Gateway transmit indoor/outdoor temperature and indoor humidity data + air quality to your phone. Transmission to Gateway every 6 minutes.

Logistical information

MA10402

Base : **MA10402**




- EAN Code : **3 7001 238 5420 3**
- Dimensions : **Dimensions of the base : 145.45 x 117 x 41.6 mm**
Dimensions of the sensor TX47-IT: 32.4 x 86.5 x 14.1 mm
- Power consumption : **Power supply of the base :2 x C LR14 1.5V (Batteries excluded)**
Power supply of the sensor : 2 x AAA LR3 (Batteries excluded)

Transmitter : **WSTX47IT+**



- EAN Code : **3 7001 238 5427 2**

Packaging & Manuals



- **Export carton**
- Export carton EAN code : **3 7001 238 3268 3**
- Export carton dimensions : **49 x 31.4 x 28.2 cm**
- Net Weight : **7.8 kg**
- Gross Weight : **8.6 kg**