

Technical sheet

RS700-BLI



ref. RS700-BLI

Ultra-quick universal battery charger until 3000
mAh

Specifications

RS700-BLI

Display ➔

- LCD Screen displaying voltage, current charge, mAh and time for each battery

Discharge ➔

- Clear your battery before charging it in order to avoid what is called the "memory effect", especially for NiCd cells.

Test function ➔

- In order to measure the exact capacity of each rechargeable battery under certain clearance conditions (from 100 to 500 mA), charge the battery until it is full and then clear it until it is empty and then charge it again.
- The capacity in mAh is displayed in real time
- By this way, bad or low capacity batteries can be identified and replaced

Features ➔

- Universal battery charger for all types of Ni-MH and Nicad batteries from 200 mAh up to 3000 mAh (milliampere-hours).
- User selectable charge of 200, 500 or 700 mA
- Individual charge is controlled by a microprocessor for voltage, current charge and temperature
- Temperature and reverse polarity detection and protection
- Overloaded and damaged battery detection and protection

Charge ➔

- Insert the battery. Select the charge by pressing the "CURRENT" button several times (from 200 to 700 mA). Leave battery until the display shows "Full"


Refresh ➔

- By consistently charging and clearing the battery at the same charge level, the user will be able to monitor the state of the battery. The maximum cycle is 50.
- By this way you can reactivate old NiCad or Ni-MH batteries.

Logistical information

RS700-BLI

Packaging & Manuals



- **Peggable Blister**
Six language manual French “
English “ German “ Italian “
Spanish “ Dutch

Export carton

- Export carton EAN code :
3 7001 238 5166 0
- Export carton dimensions :
44 x 42 x 27.5 cm
- Net Weight : **6.3 kg**
- Gross Weight : **7.2 kg**

Base : RS700-BLI



- EAN Code : **3 7001 238 5161 5**
- Dimensions : **75 x 35 x 130 mm**