

Manual time setting:

In the normal display state, press the "SET" button for 2 seconds to start setting. Press the "SET" button to change project, set the following order: 12/24 hours -Hour -Minute. Set the range according to the "
button to adjust the numbers, hours: 0-23, minutes: 0-59.

Temperature and Humidity function

In the normal display state, LCD screen will automatically display the indoor Temperature and Humidity, press the "SET" converting $^{\circ}$ C/ $^{\circ}$ F.

Temperature display range: -10 $^{\circ}$ C $^{\circ}$ +50 $^{\circ}$ C or 14 $^{\circ}$ F $^{\circ}$ 122 $^{\circ}$ F, Humidity range:20% RH $^{\circ}$ 90% RH. According to the Humidity value, five segment display tips from dry to wet.

Maximum \ Minimum Temperature and Humidity

In any interface, press the "MEM" button will switch the display to the Maximum Temperature and Humidity for 5 seconds, then the Minimum Temperature and Humidity according to press the "MEM" button again.

In the Maximum or Minimum value interface, press the "MEM" button for 2 seconds will clear the Maximum or Minimum Temperature and Humidity record.

TECHNICAL SPECIFICATIONS:

- Indoor temperature range: -10 °C ~+50 °C (14 °F ~122 °F)
- Indoor humidity range: 20% RH ~ 90% RH
- Over/Hunder range messages: "HH.H/LL.L" and "--" for temperature,
 "HH/LL" for humidity
- Resolution: 0.1° for temperature et 1% for humidity
- Indoor temperature and humidity reading updates every 20 seconds
- Minimum/Maximum temperature and humidity records
- Comfort level display :
- SEC : relative humidity is lower than 34%
- CONFORT/SEC: relative humidity is between 35% and 40%
- CONFORT/IDEAL: relative humidity is between 41% and 55%

WT139 Instruction Manual

CONFORT/HUMIDE: relative humidity is between 56% and 64%

HUMIDE: humidity is higher than 65%

- 12/24 Hour / Clock

Battery.: 2pcs x LR44 1.5v (included) Dimensions : 100 x 100 x 16 mm

LIABILITY DISCLAIMER:

- •The electrical and electronic wastes contain hazardous substances. Disposal of electronic waste in wild country and/or in unauthorized grounds strongly damages the environment.
- •Please contact your local or/and regional authorities to retrieve the addresses of legal dumping grounds with selective collection.
- •All electronic instruments must from now on be recycled. User shall take an active part in the reuse, recycling and recovery of the electrical and electronic waste.
- •The unrestricted disposal of electronic waste may do harm on public health and the quality of environment.
- •As stated on the gift box and labeled on the product, reading the "User manual" is highly recommended for the benefit of the user. This product must however not be thrown in general rubbish collection points.
- •The manufacturer and supplier cannot accept any responsibility for any incorrect readings and any consequences that occur should an inaccurate reading take place.
- •This product is designed for use in the home only as indication of the temperature.
- •The plug on the power adapter (if included) is intended to serve as the disconnect device, the socket-outlet shall be installed near the equipment and shall be easily accessible.
- •This product is not to be used for medical purposes or for public information.
- •The specifications of this product may change without prior notice.
- •This product is not a toy. Keep out of the reach of children.
- •No part of this manual may be reproduced without written authorization of the manufacturer.



WT139 Instruction Manual



RED DIRECTIVE 2014/53/EU

Summary of the Declaration of Conformity: We hereby declare that this wireless transmission device does comply with the essential requirements of RED Directive 2014/53/EU.

LA CROSSE TECHNOLOGY

6 A RUE DU COMMERCE

67118 GEISPOLSHEIM

FRANCE